

► Features

- Easy to install
- Flexible and reliable
- Low power consumption
- Small and light weight device
- High light intensity

► Applications

To be used together with the AUDAC CSE55

- Fire departments
- Noisy factories
- Wide variation of emergency situations



The CSE100 is the LED (24 V DC) that is integrated into the AUDAC's CSE55 ceiling speaker.

The CSE55 is AUDAC's single cone loudspeaker with an integrated red signal LED (which emits a visual evacuation signal) and idle current control.

The speaker combines professional audio equipment with great design and comfort. The ceiling speaker is specially designed to deliver high-quality speech reproduction, but can also be used for background music.

The CSE100 can also be acquired separately. The device emits light when an electrical power of 24 V DC is applied.

The LED meets the requirements for high flexibility and reliability of signalling equipment.

► Specifications

PRODUCT FEATURES	
Dimensions (Diameter x Height)	Ø 44 mm x 24 mm
Power	24 V DC
Current	45 mA
Angle	120°
Light intensity	24 Lumen
Weight	17 g
Housing	White ABS bottom with transparent cap
Length connection cables	80 mm
SHIPPING & ORDERING	
Packaging	???
Shipping weight & volume	20 g
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	