

Optional adapter that allows a wireless network LAN connection.



USBWL11N - Front



USBWL11N - Back

Complete Specifications

Interface: USB 2.0	Dimensions: Width – 0.7" (17 mm) Not including protruding parts Length – 1.3" (33 mm) Depth – 0.3" (8 mm)
Standard: IEEE802.11 b/g/n	Compatible with the following models:
Frequency: 2.4 GHz ISM band	A: CP-WU9410/WU9411, CP-HD9320/HD9321, CP-WX9210/WX9211, CP-X9110/X9111, CP- WU8461, CP-WX8265, CP-X8170, CP-WU8451, CP-WU8440, CP-WX8255A, CP-X8160, CP-WX4022WN, CP-X5022WN
Connection: Infrastructure Mode Adhoc Mode (for PJ category A) Simple Access Point Mode (for PJ category B)	B: CP-TW3005, CP-TW2505, CP-AX2505, CP-AX3505, CP-AW2505, CP-AW3005, CP-BW301WN, CP-BX301WN, CP-WX4041WN, CP-WX3541WN, CP-WX3041WN, CP-X4041WN, CP-X3041WN, CP-X2541WN
Security: WEP (64 bit/128 bit)* <i>*WEP(64bit/128bit) is not supported with Simple Access Point Mode.</i> WPA-PSK (AES/TKIP), WPA2-PSK (AES/TKIP)	

USBWL11N