# SMS FLATSCREEN **X** CH SD605/1105/1455/1955



The highest degree of freedom – doubled.

rear of the column, as an option.

A ceiling bracket that provides extra possibilities by allowing two screens to be placed back-to-back. The screens can be mounted on the bracket in both a vertical and a horizontal position. The screens can be easily swivelled to allow viewing from any part of the room. The screens are mounted using ingenious and secure universal fittings. Electrical power sockets can be installed on the

The X series is characterised by clean and refined features. The cable holder, for example, into which it is easy to place all cables by hand. The surface finish has also been given extra attention.

## SMS FLATSCREEN X - CH SD605/1105/1455/1955

#### INFO

- Finish: A/W (Aluminium/white).
- Max. load: 50 kg/screen. The optional accessory SMS X H+ Unislide enables the bracket to bear up to 100 kg/screen.
- Length (column): 605, 1105, 1455 or 1955 mm.
- Swivel: +/-180°.

Delivered as standard with our Unislide – SMS X H Unislide, which can be used with all VESA standards from  $200 \times 200$  to  $800 \times 400$  mm. (Screens ~40-55"). The SMS X H+ Unislide is available as an option. This can be used with all VESA standards from  $200 \times 200$  to  $1200 \times 700$  mm. (Screens ~60-80").

### ART. NO

PD061005-P0 PD061006-P0 PD061007-P0 PD061008-P0

P0 SMS Flatscreen X CH SD605 A/W
P0 SMS Flatscreen X CH SD1105 A/W
P0 SMS Flatscreen X CH SD1455 A/W
P0 SMS Flatscreen X CH SD1955 A/W

DESCRIPTION

#### ACCESSORIES:

PD100001	SMS Power Socket EU (Schuko)
PD100002	SMS Power Socket CH
PD100003	SMS Power Socket UK
PD210002	SMS X H+ Unislide*
PD300005-P0	SMS X Shelf White*
PD300006-P0	SMS X Shelf Oak*
PD300007-P0	SMS X Shelf Walnut*
PD400001	SMS X Media Box White*
PD400003	SMS X Media Box Oak*
PD400004	SMS X Media Box Walnut*
PD410001	SMS X Media Box Rack Accessory*

\*More info in separate data sheet.







Tilt -29

Shelves available as an option.

Rotatable, discrete, Electrical power sockets secure attachment. can be mounted at the rear.

314 mm <u>270</u> mm 88 mm 2065 E C F 1955 215 1455 -105 ų, •@• 200 mr 250 mm ΤМ



SMART MEDIA SOLUTIONS

www.SmartMediaSolutions.se