

## Highlights:

---

- 2000 Watt program power
- Low frequency extension down to 26Hz without processing
- 124 dB of Max SPL (continuous)
- Indoor model with Polyurea coated 18/36mm multiply plywood
- Weather resistant with marine grade plywood and Dura-Polyurea coating
- Extremely ridged chassis and inner framing

## Product information:

---

Engineered for demanding environments such as nightclubs, concert venues, theme parks, and hospitality spaces, the BASSO Series combines cutting-edge technologies like the pure carbon fiber cone and AeroVent for exponential low-noise venting with meticulous craftsmanship to set a new standard in low-frequency fidelity.

With a focus on ultra-high power output and exceptional sound clarity, the BASSO Series offers a flexible, efficient solution for diverse applications. Each model is designed to deliver a visceral sound experience with immersive infra-sub performance and extremely low distortion.

## Applications:

---

- Bars & Restaurants
- Hotels
- Clubs
- Sporting facilities
- Events
- Concert venues
- Museums & Themeparks



## Properties:

---

 Weatherproof

## Impedance:

---

$\Omega$  8 Ohm

## Usage:

---

 Indoor  Outdoor

## System specifications:

---

Speaker type	12" Infra-Sub	
Configuration	AeroVent	
Peak power handling	4000 W	
Program power handling	2000 W	
Continuous power (AES)	1000 W	
Impedance	8 $\Omega$	
Max SPL (Continuous)	124 dB	
Sensitivity (1W/1m)	94 dB	
Frequency	Response (- 3 dB)	33 Hz - 120 Hz
	Range (-10 dB)	26 Hz - 200 Hz
Bass port tuning frequency	39 Hz	
Connectors	Terminal block with linkthrough	
Drivers	12" carbon cone with dual suspension (low-loss) and 3.5" high excursion voice coil	
Ingress Protection rating	IP55 (BASSO112/OB)	

## Product Features:

---

Dimensions	608 x 366 x 595 mm (W x H x D) (excluding feet)	
	608 x 371 x 595 mm (W x H x D) (including feet)	
Weight	26 kg	
Operating temperature	-20 °C ~ 70 °C	
Construction	18 mm Multiply Plywood with multi-layer Polyurea coating	
Front finish	2.0 mm Steel grill with hexagon perforations and acoustic foam backing	
Mounting & handling	Rigging points	8 x M10 mounting bracket installation holes on both sides
Colours	Black	
Mounting & handling	Stand fitting	1 x M20 internal thread stand adapter

## Variants:

---

- BASSO112/B - Black version
- BASSO112/OB - Outdoor black version